

ExCam XF Q1645 Explosion-Protected Network Camera

Every detail counts in hazardous areas

ExCam XF Q1645 Explosion-Protected Network Camera is an easy-to-install and easy-to-integrate fixed box camera. It delivers high-resolution video (2 MP) at full frame rate (up to 120 fps) for crystal-clear images. The electronic image stabilization greatly improves video quality where the camera is subject to vibrations. The camera is adapted for explosion-prone applications with ATEX, IECEx, EAC Ex, and IA certifications. With low weight, PoE support for plug-and-play installation, ExCam XF Q1645 offers significant savings. The camera helps detecting unauthorized individuals and monitor employee safety in hazardous areas. Suitable for onshore, offshore, marine, and heavy industrial environments.

- > **Certified for ATEX, IECEx, EAC Ex, and IA; Zones 1, 2, 21, and 22; Groups IIC and IIIC**
- > **Cost-efficient installation with PoE**
- > **HDTV 1080p at 100/120 fps**
- > **Unparalleled light sensitivity with 1/2" sensor**
- > **Electronic image stabilization (EIS) and low weight**



ExCam XF Q1645 Explosion-Protected Network Camera

Camera		External output activation, day/night vision mode, status LED, WDR mode, Defog mode, PTZ control
Image sensor	1/2" progressive scan RGB CMOS	
Lens	IR corrected i-CS lens Varifocal 3.9–10.0 mm, F1.5 Horizontal field of view: 85°–42° Vertical field of view: 47°–23°	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	HDTV 1080p 25/30 fps: Color: 0.03 lux, B/W: 0.01 lux, SNR: 0.03 lux, at 50 IRE F1.5 HDTV 1080p 25/30 fps (WDR off): Color: 0.02 lux, SNR: 0.02 lux, at 50 IRE F1.5	
Shutter time	1/100000 to 2 s	
Pan/Tilt/Zoom	Digital PTZ, uploadable PTZ driver (Pelco D pre-installed)	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC), Main, Baseline and High Profile Motion JPEG	
Resolution	1920x1080 to 320x180	
Frame rate	Up to 100/120 fps (50/60 Hz) in 1920x1080 (no WDR)	
Video streaming	Multiple, individually configurable streams in H.264 and Motion JPEG Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/MBR H.264	
Image settings	Saturation, contrast, brightness, sharpness, Forensic WDR – 120 dB, white balance, day/night threshold, exposure mode, exposure zones, compression, orientation: auto, 0°, 90°, 180°, 270° including Corridor Format, mirroring of images, text and image overlay, privacy masks, defogging, noise reduction, electronic image stabilization, barrel distortion correction, orientation aid, fine tuning of behavior at low light Scene profiles: forensic, live, traffic overview, backlit entrance	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1X ^a network access control, digest authentication, user access log, centralized certificate management, brute force delay protection	
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF Profile S and ONVIF Profile G, specifications at onvif.org	
Analytics	Included AXIS Video Motion Detection, active tampering alarm, AXIS Fence Guard, AXIS Motion Guard Supported AXIS Digital Autotracking, AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
Event triggers	Analytics, external input, edge storage events Detectors: live stream accessed, video motion detection, shock detection Hardware: network, temperature Input Signal: manual trigger, virtual inputs PTZ: error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: recurrence, use schedule	
Event actions	File upload: FTP, SFTP, HTTP, HTTPS, network share and email, send video clip Notification: email, HTTP, HTTPS and TCP Overlay text, Send SNMP Trap Video recording to edge storage Pre- and post-alarm video buffering	
Data streaming	Event data	
Built-in installation aids	Remote focus and zoom with supplied i-CS lens Traffic wizard, pixel counter, levelling assistant	
General		
Casing	IP68-rated, SS 1.4404 (ASTM 316L) stainless steel casing for maximum corrosion protection. Casing manufactured and certified by Samcon Prozessleittechnik GmbH, www.samcon.eu	
Sustainability	PVC free	
Memory	1 GB RAM, 512 MB Flash	
Power	Camera: Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.5 W, max 9.1 W Heater: 24 V DC, max 40 W 24 V DC is required for operating at temperatures below 0 °C (32 °F).	
Connectors	EXTB-3 Junction Box ExCam: 10 terminal clamp UT 2.5 2 conductor terminal USLKG 5	
Storage	Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Operating conditions	-60 °C to 60 °C (-76 °F to 140 °F) Humidity 10–100% RH (condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)	
Approvals	EMC EN 55032 Class A, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 62479, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11 Environment IEC/EN 60529 IP68, IEC/EN 62262 IK10 Explosion DIN EN/IEC 60079-0, DIN EN/IEC 60079-1, DIN EN/IEC 60079-7, DIN EN/IEC 60079-31, TR CU 012/2011, GOST R IEC 60079-0, GOST IEC 60079-1, GOST R IEC 60079-7, GOST R IEC 60079-31 Network NIST SP500-267	
Certifications	Camera: Model key: T08-VA2.3.K3.B0R2-LL.H-005.A-T ATEX: II 2 G Ex db IIC T5 Gb, Ex II 2 D Ex tb IIIC T95°C Db, I M2 Ex db I Mb Certificate: TÜV 18 ATEX 8218X IECEx: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db, Ex d I Mb Certificate: IECEx TUR 18.0023X IA: Ex db IIC T5 Gb, Ex tb IIIC T95°C Db, Ex d I Mb Certificate: MASC MS/18-3256X EAC Ex: 1Ex db IIC T5 Gb, Ex tb IIIC T95°C Db, PB db I Mb Certificate: RU C-DE.AB61.B.00381/19 EXTB-3 Junction Box ExCam: (to be removed if the camera is installed in mines) Model key: T12-3M20 ATEX: II 2 G Ex eb IIC T5 Gb, II 2 D Ex tb IIIC T95°C Db IP66, -50°C < Tamb < +55°C Certificate: PTB 99 ATEX 3103 IECEx: Ex e IIC T5 Gb, Ex IIIC T95°C Db IP66, -50°C < Tamb < +55°C Certificate: IECEx PTB 06.0026 EAC Ex: 1Ex e IIC T5 Gb X, Ex tb IIIC T95°C Db X Certificate: RU C-DE.AA71.B.00120	
Dimensions	357 x 113 x 139 mm (14.06 x 4.45 x 5.5 in)	
Weight	10.8 kg (23.8 lb)	
Included accessories	Weathershield ExCam XF, Installation Guide, Windows decoder 1-user license, ASKDPO3-T Cable ExCam 5 m (16 ft), EXTB-3 Junction Box ExCam, AXIS Surveillance microSDXC Card 128 GB	
Optional accessories	Wall Mount ExCam XF, Pole Mount ExCam XF Non-armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft), Armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft)	

Ex Connection Rail 4-port PoE PS 24,
Ex Connection Rail 8-port PoE PS 24
For more accessories, see axis.com

Video management software	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available on axis.com/vms
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese

Warranty Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>), and cryptographic software written by Eric Young (ey@cryptsoft.com).*

Environmental responsibility:
axis.com/environmental-responsibility